

WINNER[®]

BATTERY
SWITCH FOR SUCCESS

PREMIUM

Total Solutions System **STARTING BATTERIES**



- Exclusive patented lid with gas separator
- Consistent starting performance
- Extremely low rate of self discharge
- Longer lifetime by minimizing vibrations
- 30% more starting power



www.winnerbattery.net

CALCIUM TECHNOLOGY SEALED BATTERY

Type No	Capacity	Cranking	Dimensions				Construction		Base
	20 hr. rate	performance	(mm)				Layout	Terminal	Hold-down
DIN	(AH)	EN (A)	L	W	H	T.H.			
54317	43	400	207	175	175	175	0	C	B3/B4
54536	45	430	207	175	175	175	0	A	B3/B4
55066	50	420	207	175	190	190	0	A	B3/B4
55557	55	500	244	175	175	175	0	A	B3/B4
56219	62	535	244	175	190	190	0	A	B3/B4
56221	62	535	244	175	190	190	1	A	B3/B4
56530	65	560	277	175	175	175	0	A	B3/B4
56638	66	540	277	175	190	190	0	A	B3/B4
57539	75	650	277	175	175	175	0	A	B3/B4
57540	75	640	277	175	190	190	0	A	B3/B4
57541	75	640	277	175	190	190	1	A	B3/B4
58046	80	720	313	175	175	175	0	A	B3/B4
59043	90	800	313	175	190	190	0	A	B3/B4
60038	100	760	353	175	190	190	0	A	B3/B4
60285	102	750	330	175	220	240	1/0	A	
60285T	102	750	330	175	220	240	1/0	F	
63530	135	1005	505	182	210	234	3	A	
66514	160	1090	508	215	210	234	3	A	
71014	210	1100	510	275	218	238	3	A	
72512	225	1200	510	275	218	238	3	A	
73027	230	1400	510	275	218	238	3	A	
JIS									
53520	35	300	187	127	200	220	0	B	
53522	35	300	187	127	200	220	1	B	
54035	40	300	190	139	200	220	0	B	B1
54523	45	360	236	128	200	220	0	A	
54524	45	360	236	128	200	220	1	A	
54551	45	360	236	128	200	220	1	B	
54584	45	360	236	128	200	220	0	B	
55041	50	400	206	172	183	205	0	A	B1
55042	50	400	206	172	183	205	1	A	B1
56068	60	500	230	168	200	220	0	A	B1
56069	60	500	230	168	200	220	1	A	B1
57024	70	550	260	168	200	220	1	A	B5
57029	70	550	260	168	200	220	0	A	B5
59017	90	600	303	172	203	225	0	A	B1
59018	90	600	303	172	203	225	1	A	B1
60032	100	780	303	172	203	225	0	A	B1
60033	100	780	303	172	203	225	1	A	B1
BCI RC									
34-750	115	750	260	172	186	206	1	A	B1
58-520	80	520	260	180	157	177	1	A	B1
65-700	130	700	305	189	172	192	1	A	B1
75-530	90	530	239	179	186	186	1	E	B1
78-630	105	630	269	179	180	205	1	E	B1

More types available on request

