

WINNER®

BATTERY
SWITCH FOR SUCCESS

SPRINT

Total Solutions System

STARTING BATTERIES



www.winnerbattery.com

Type No	Capacity	Cranking	Dimensions				Construction		Base
	20 hr. rate	Performance	(mm)				Layout	Terminal	
DIN	(Ah)	EN (A)	L	W	H	T.H			
530 030 030	30	300	195	130	168	183	0	D	
530 034 030	30	300	195	130	168	183	1	D	
536 046 030	36	300	210	175	175	175	0	A	B3/B4
540 108 030	40	300	175	175	190	190	0	A	B3
544 059 036	44	360	210	175	190	190	0	A	B3
545 065 039	45	390	210	175	175	175	0	A	B3/B4
550 059 042	50	420	210	175	190	190	0	A	B3
555 057 048	55	480	242	175	175	175	0	A	B3/B4
555 059 048	55	480	242	175	190	190	0	A	B3
555 065 048	55	480	242	175	190	190	1	A	B3
562 019 054	62	540	242	175	190	190	0	A	B3
563 018 056	63	560	278	175	175	175	0	A	B3/B4
566 038 054	66	540	278	175	190	190	0	A	B3/B4
572 013 064	72	640	278	175	175	175	0	A	B3/B4
572 020 064	72	640	278	175	190	190	0	A	B3
575 039 065	75	650	278	175	175	175	0	A	B3
580 046 068	80	680	310	175	175	175	0	A	B3/B4
590 043 076	90	760	315	175	190	190	0	A	B3
600 038 076	100	760	353	175	190	190	0	A	B3

SWIFT CRANKING PERFORMANCE BATTERY

Type No	Capacity 20 hr. rate	Cranking Performance	Dimensions (mm)				Construction		Base Hold-down
			L	W	H	T.H	Layout	Terminal	
DIN	(Ah)	EN (A)							
600 044 085	100	850	353	175	190	190	0	A	B3
635 044 085	135	850	513	175	208	208	3	A	B3
640 020 085	140	850	511	187	200	220	3	A	
670 018 090	170	900	513	222	200	220	3	A	
680 025 100	180	1000	513	222	200	220	3	A	
700 027 105	200	1050	518	273	221	241	3		
730 011 110	230	1100	518	273	221	241	3	A	
JIS									
535 020 030	35	300	197	129	204	224	0	B	
535 022 030	35	300	197	129	204	224	1	B	
535 035 030	35	300	197	129	204	224	0	B	B1
545 023 036	45	360	238	129	205	225	0	A	
545 024 036	45	360	238	129	205	225	1	A	
545 051 036	45	360	238	129	205	225	1	B	
545 077 036	45	360	238	128	205	225	0	A	B1
545 079 036	45	360	238	128	205	225	1	A	B1
545 084 036	45	360	238	129	205	225	0	B	
560 068 050	60	500	232	173	205	225	0	A	B1
560 069 050	60	500	232	173	205	225	1	A	
570 024 060	70	600	260	173	202	222	1	A	B5
570 029 060	70	600	260	173	202	222	0	A	B5
575 024 064	75	640	260	173	202	222	1	A	B5
575 029 064	75	640	260	173	202	222	0	A	B5
600 026 076	100	760	410	175	215	235	0	A	
600 031 076	100	760	330	173	220	240	1/0	E	
600 032 068	100	680	303	173	205	225	0	A	B1
600 033 068	100	680	303	173	205	225	1	A	B1
600 037 076	100	760	330	173	220	240	1/0	A	
620 047 095	100	950	330	173	220	240	1/0	A	
BCI									
75-530	60	530	231	176	185		1	E	B1
78-630	70	630	269	179	205		1	E	B1
65-700	85	700	295	189	192		1	A	B1
MARINE									
600 031 076	100	760	330	173	220	240	1/0	E	

- Calcium technology sealed closed type range
- Long life duration - Low self-discharge
- Swift cranking performance for car batteries
- Widest range according to EN, JIS and BCI specifications with types from 30Ah to 230Ah
- Strong plate design for truck batteries

