

Total Solutions System **STATIONARY BATTERIES**



WINNER[®]

BATTERY
SWITCH FOR SUCCESS

AGM DEEP CYCLE

- Deep cycle VRLA AGM 2/6/12 Volts rechargeable blocks
- Excellent cyclic & anti-vibration performance
- High specific energy design with high purity materials
- More than 800 cycles with 50% D.O.D.
- Design service life is 10 years at 25°C



www.winnerbattery.net

PROTEUS

SEALED VRLA MF RECHARGEABLE BATTERY



150-12 (12 Volts, 150AH/10HR)
SEALED VRLA MAINTENANCE-FREE RECHARGEABLE BATTERY

DEEP CYCLE

TYPE	VOLTAGE REGULATION	INITIAL CURRENT
STAND BY USE	13.8-13.9V	45A
CYCLE USE	14.4-14.7V	45A

CAUTION
Do not charge in a gas tight container.
Do not operate in explosive atmosphere.
Do not short circuit or connect
together with another cell.
Do not use in a fire or flame.
Do not use in a fire or flame.


Nonspillable

RECYCLE
Pb
RU
CE

Type No	Voltage	Capacity	Max Discharge Current in 5"	Dimensions (mm)				Layout	Terminal	Weight
	V	AH (C10)	A	L	W	H	T.H.			(kg)
180-6	6	180	1800	306	168	222	227	2	F18	26,50
200-6	6	200	2000	260	180	247	252	2	F18	30,00
225-6	6	225	2250	244	188	275	275	2	F18	32,00
225-6B	6	225	2250	322	178	225	230	2	F18	32,00
12-12	12	12	120	150	98	95	100	3	F2	4,20
18-12	12	18	180	181	76	167	167	0	F3-F12	5,90
26-12	12	26	260	166	175	125	125	0	F3-F12	8,10
35-12	12	35	350	196	131	159	180	1	F13	10,20
45-12	12	45	450	198	166	171	171	0	F13	15,50
55-12	12	55	550	229	138	210	215	1	F13	18,00
75-12	12	75	750	260	169	210	215	1	F13	23,50
80-12	12	80	800	350	167	180	183	1	F13	24,00
100-12	12	100	1000	307	169	210	215	1	F18	30,00
120-12	12	120	1200	328	172	222	227	1	F18	32,50
120-12B	12	120	1200	407	178	225	230	1	F18	36,00
145-12	12	145	1450	340	173	280	285	1	F18	44,00
150-12	12	150	1500	483	170	231	241	1	F18	45,00
180-12	12	180	1800	530	209	214	219	4	F18	53,00
200-12	12	200	2000	522	240	219	224	4	F18	60,00
260-12	12	260	2600	522	268	219	224	4	F18	74,00
200-2	2	200	1000	171	107	330	365	5	F17	14,00
300-2	2	300	1500	171	151	330	365	5	F17	19,00
400-2	2	400	2000	211	175	330	365	5	F17	26,00
500-2	2	500	2500	242	175	330	365	5	F17	30,50
600-2	2	600	3000	302	175	330	365	5	F17	37,00
800-2	2	800	3200	410	175	330	365	6	F17	50,00
1000-2	2	1000	4000	475	175	330	365	6	F17	62,00
1200-2	2	1200	4800	475	175	330	365	6	F17	76,00
1500-2	2	1500	6000	401	350	340	382	9	F17	96,00
2000-2	2	2000	7000	490	350	340	382	9	F17	127,00
3000-2	2	3000	9000	710	350	340	382	10	F17	193,00

More types available on request

KEY FOR LAY OUT



APPLICATIONS

- Wheelchairs – Scooters - Lawn mowers
- UPS systems - Road lights
- Off-Grid solar systems
- Marine signaling/service applications

KEY FOR LAY OUT

